



# AMERICAN SHINGLES

a g r e a t d e s i g n a l t e r n a t i v e

AMERICAN SHINGLES PTY LIMITED

NATIONAL OFFICE:  
UNIT 26, 56 O'RIORDAN STREET  
ALEXANDRIA NSW 2015

TELEPHONE: 1300 131 881  
FACSIMILE: 1300 731 881

EMAIL: [info@americanshingles.com.au](mailto:info@americanshingles.com.au)

## TECHNICAL DATA SHEET

# GRAND MANOR SHANGLE®

### 1. PRODUCT NAME:

Grand Manor Shangle Roofing Shingles  
Grand Manor Shangle AR Roofing Shingles

### 2. MANUFACTURER:

CertainTeed Corporation  
Roofing Products Group  
750 E. Swedesford Road  
P.O. Box 860  
Valley Forge, PA 19482  
[www.certainteed.com](http://www.certainteed.com)

### DISTRIBUTOR (Australia/Oceania/SE Asia):

American Shingles Pty Limited  
National Office:  
Unit 26, 56 O'Riordan Street  
Alexandria NSW 2015  
Telephone: 1300 131 881 Int'l: +61 2 9317 3553  
Facsimile: 1300 731 881 Int'l: +61 2 9317 3551

### 3. PRODUCT DESCRIPTION:

This product is the super heavyweight of laminated shingles. The difference is in the size and quality built-in by design. An 203mm (8") tab area, complete with two full-sized one-piece base shingles with random tabs and accented by shadow lines, gives an authentic, natural look with true depth and dimension. They are most aesthetically appealing when used on slopes of 35° (9" per foot) or greater. When applied, Grand Manor produces five layers of roof protection and the quality is reminiscent of handcrafted workmanship. It is designed to resist blow off in high winds up to 175km/h (110mph).

Grand Manor Shangle AR shingles are algae (commonly called fungus) resistant and thus protect against staining or discoloration caused by algae.

Grand Manor shingles are available in the following colours: Black Pearl, Brownstone, Colonial Slate, Gatehouse Slate, Georgian Brick, Heirloom Silver, Sherwood Forest, and Stonegate Grey.

Pre-cut Grand Manor Shangle/Carriage House Shangle Accessory roofing shingles of the matching colour are to be used for capping the hips and ridges. These accessory shingles are two layers adhered together and do not have the additional random tabs.

**Limitations:** Use on roofs with slopes greater than 9.5° (2" per foot). However, slopes greater than 35° (9" per foot) best show the product design. Low slope applications 9.5° to 18.5° (2" to 4" per foot) require additional underlayment. In areas where icing along the eaves can cause the back-up of water, applying CertainTeed WinterGuard™ Waterproofing Shingle Underlayment, or its equivalent, according to application instructions provided with the product and on the shingle package.

On slopes greater than 60° (21" per foot), apply three 25mm (1") diameter spots of asphalt roofing cement (ASTM D 4586, Type II) under the shingle, according to application instructions provided with the product and the shingle package.

**Composition and Materials:** Grand Manor shingles are composed of a fibreglass mat base. Ceramic-coated mineral granules are tightly embedded in carefully refined, water-resistant asphalt. The laminated tabs are firmly adhered in a special tough asphaltic cement. These fibreglass-based shingles have self-sealing adhesive applied.

Importers of quality roofing shingles, shakes and rainwater products



